Part 2-D) Installation with Tsukayu adaptive brackets & plates assembly kit

(xii) Honda VT750 Shadow Phantom

Two hardware kits are needed: a) TSU802P adaptive brackets kit; b) D11 bracket plates assembly kit





Fig. 2-D-(xii)-1

TSU802P adaptive brackets kit includes
(Refer to Fig. 2-D-(xii)-1):

- (A1) TSU802_p1 left x 1pc
- (A2) TSU802_p1 right x 1pc
- (A3) TSU802_p2 left x 1pc
- (A4) TSU802_p2 right x 1pc
- (A5) MS_NUT x 6pcs
- (A6) M6 x 20mm bolt cylinder head x 4pcs
- (A7) M6 x 20mm bolt cylinder head x 2pcs
- (A8) spacer 3mm(L) x6.5mm(I) x19mm(O) x 4pcs
- (A9) Bolt M6 x 15mm (hex head) x 2pcs
- (A10) Bolt M8 x 15mm (hex head) x 2pcs
- (A11) Bolt M8 x 40mm (hex head) x 2pcs
- (A12) spacers 11.5mm(L) x 8.5mm(I) x 16mm(O) x 2pcs
- (A13) M8 washers x 4pcs
- (A14) M6 washers x 2pcs
- (A15) MS1_ver3 spacers x 2pcs

Fig. 2-D-(xii)-2



D11 bracket plates kit includes
(Refer to Fig. 2-D-(xii)-2)

- (B1) D11 left x 1pc
- (B2) D11 right x 1pc
- (B3) MS1_ver3 spacers x 4pcs
- (B4) spacer 20mm(L) x6.5mm(I) x13mm(O) x 4pcs
- (B5) Bolt M8 x 50mm (round head) x 4pcs
- (B6) additional M6 washers (use if necessary)
- (B7) M6 lock washers x 4pcs

1. Cover gas tank and front fender with protective material.

2. Install the TSU802p bracket assembly as shown in Fig.2-D-(xii)-1, the turn signal bar should be removed temporarily (turn signal bar is not shown in the figure). Measure the distance between the slots on left and right quick release latches, this distance will be used to adjust the distance between the bracket plates on fairing, you need to measure it as accurate as possible, we suggest measuring in mm.

*3. Install the mounting plates assembly as shown in Fig.2-D-(xii)-2. Add M6 washers if the distance of the two mounting plates doesn't perfectly match the distance between the two slots of D11. The spacers provided are close to what you need, but you may still need to add washers until they perfectly match, make sure you use same number of spacers and washers for all holes. Don't mix up Left and Right bracket plates, the latches come with the bracket plates. Try to put the fairing on, normally you will need to modify the number of washers several times until they match.

4. Now put the fairing on, you may need a helper for doing this step easier. Make sure the bracket plates are tightened securely. Latch the both side bracket plates securely. Tighten all the bolts on the fairing and all bolts on the whole mounting system.

Copyright © Tsukayu - All rights reserved